

OnCue™ Series

SPECIALTY CHEF LINE

MOC524I - 2400 Watts

FEATURES AND BENEFITS

- 2400 watts of power
 - Fast heating = more customer turns= more revenue & profits
- 8.4 L (0.3 cubic ft.) oven capacity
 - Accommodates a 152 mm (6") deep ¼ size pan
- Top and bottom antenna system
 - Dispersed energy pattern for even cooking
 - Consistent results and excellent food quality
- 100 programmable menu items, 4 cooking stages, 11 power levels
 - Delivers consistent, quality results
- Unique pop up door
 - Uninterrupted kitchen traffic
 - Operators are visually cued when food is ready
- Ergonomic design for one-touch cooking
 - Close door and select keypad in one motion
- Jigsaw shaped footprint
 - Doubles productivity on a 724 mm (28 ½") shelf



Angled control panel is easy to view and operate

Unique pop up door



IDEAL APPLICATIONS

- Quick service restaurants
- Fast casual restaurants
- Casual dining

BOOST HEATS & RE-THERMS IN SECONDS!

- 1 min 30 sec – heats 170g (6 oz.) spinach dip from frozen
- 4 sec – boost heat 1 prepared 142g (5 oz.) cheeseburger
- 20 sec – re-therm 1 refrigerated 142g (5 oz.) breakfast croissant
- 1 min 10 sec – defrost and re-therm 198g (7 oz.) mac 'n cheese

OnCue™
Ready When You Are

MENUMASTER®
Commercial

SPECIFICATION COMPARISON

MENUMASTER® COMMERCIAL MICROWAVE OVENS

MODEL / UPC CODE	WATTS	POWER SOURCE	PLUG TYPE	CABINET DIMENSIONS (H X W X D)**	CAVITY DIMENSIONS (H X W X D)	CAPACITY	SHIPPING DIMENSIONS (H X W X D)	SAFETY LISTING	SANITATION LISTING	WEIGHT PROD./SHIP
MSO5353 728028315943	3500*	400V, 50Hz, Wye, 16A, 3 phase, 5 wire	IEC 309	472×650×597mm (18 $\frac{1}{8}$ ×25 $\frac{3}{8}$ ×23 $\frac{1}{2}$ in.)	251×535×330mm (9 $\frac{7}{8}$ ×21×13in.)	45L (1.6ft ³)	565×768×667mm (22 $\frac{1}{4}$ ×30 $\frac{3}{4}$ ×26 $\frac{1}{4}$ in.)	CE	ETL Intertek	66/73kg (146/161 lbs)
MSO5351 728028315837	3500*	230-240V, 50Hz, 30A, single phase	IEC 309	472×650×597mm (18 $\frac{1}{8}$ ×25 $\frac{3}{8}$ ×23 $\frac{1}{2}$ in.)	251×535×330mm (9 $\frac{7}{8}$ ×21×13in.)	45L (1.6ft ³)	565×768×667mm (22 $\frac{1}{4}$ ×30 $\frac{3}{4}$ ×26 $\frac{1}{4}$ in.)	CE	ETL Intertek	66/73kg (146/161 lbs)
MSO5211 728028315820	2100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	472×650×597mm (18 $\frac{1}{8}$ ×25 $\frac{3}{8}$ ×23 $\frac{1}{2}$ in.)	251×535×330mm (9 $\frac{7}{8}$ ×21×13in.)	45L (1.6ft ³)	565×768×667mm (22 $\frac{1}{4}$ ×30 $\frac{3}{4}$ ×26 $\frac{1}{4}$ in.)	CE	ETL Intertek	66/73kg (146/161 lbs)
MOC5241 705105607306	2400*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	448×346×487mm (17 $\frac{5}{8}$ ×13 $\frac{5}{8}$ ×19 $\frac{3}{16}$ in.)	130×298×216mm (5 $\frac{1}{8}$ ×11 $\frac{3}{4}$ ×8 $\frac{1}{2}$ in.)	8.4L (0.3ft ³)	524×432×559mm (20 $\frac{5}{8}$ ×17×22in.)	CE	ETL Intertek	32/33kg (70/73 lbs)
DEC21E2 719881167718	2100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	343×419×574mm (13 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×22 $\frac{5}{8}$ in.)	171×330×305mm (6 $\frac{3}{4}$ ×13×12in.)	17L (0.6ft ³)	473×556×625mm (18 $\frac{5}{8}$ ×21 $\frac{7}{8}$ ×24 $\frac{5}{8}$ in.)	CE	ETL Intertek	30/34kg (67/74 lbs)
DEC18E2 719881159317	1800*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	343×419×574mm (13 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×22 $\frac{5}{8}$ in.)	171×330×305mm (6 $\frac{3}{4}$ ×13×12in.)	17L (0.6ft ³)	473×556×625mm (18 $\frac{5}{8}$ ×21 $\frac{7}{8}$ ×24 $\frac{5}{8}$ in.)	CE	ETL Intertek	30/34kg (67/74 lbs)
DEC14E2 728028043181	1400*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	343×419×574mm (13 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×22 $\frac{5}{8}$ in.)	171×330×305mm (6 $\frac{3}{4}$ ×13×12in.)	17L (0.6ft ³)	473×556×625mm (18 $\frac{5}{8}$ ×21 $\frac{7}{8}$ ×24 $\frac{5}{8}$ in.)	CE	ETL Intertek	30/34kg (67/74 lbs)
RFS518TS 728028043181	1800*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	365×551×533mm (14 $\frac{3}{8}$ ×21 $\frac{3}{4}$ ×20in.)	226×359×413mm (8 $\frac{7}{8}$ ×14 $\frac{1}{8}$ ×16 $\frac{1}{4}$ in.)	34L (1.2ft ³)	467×663×581mm (18 $\frac{1}{2}$ ×26 $\frac{1}{8}$ ×22 $\frac{3}{4}$ in.)	CE	ETL Intertek	32/35kg (69/76 lbs)
RCSS1ITS 728028020762	1100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	352×559×483mm (13 $\frac{7}{8}$ ×22×19in.)	216×368×381mm (8 $\frac{1}{2}$ ×14 $\frac{1}{2}$ ×15in.)	34L (1.2ft ³)	422×640×502mm (16 $\frac{5}{8}$ ×25 $\frac{3}{16}$ ×19 $\frac{3}{4}$ in.)	CE	ETL Intertek	18.6/21.8kg (41/48 lbs)
RCSS1DSE 728028129489	1100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	352×559×483mm (13 $\frac{7}{8}$ ×22×19in.)	216×368×381mm (8 $\frac{1}{2}$ ×14 $\frac{1}{2}$ ×15in.)	34L (1.2ft ³)	422×640×502mm (16 $\frac{5}{8}$ ×25 $\frac{3}{16}$ ×19 $\frac{3}{4}$ in.)	CE	ETL Intertek	18.6/21.8kg (41/48 lbs)
RMS510TS2 728028470246	1000*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	310×512×403mm (12 $\frac{1}{4}$ ×20 $\frac{1}{8}$ ×15 $\frac{7}{8}$ in.)	197×330×330mm (7 $\frac{3}{4}$ ×13×13in.)	23L (0.8ft ³)	381×584×457.2mm (15×23×18in.)	CE	ETL Intertek	13.6/16.8kg (30/37 lbs)
RMS510DS2 728028470215	1000*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko"	310×512×403mm (12 $\frac{1}{4}$ ×20 $\frac{1}{8}$ ×15 $\frac{7}{8}$ in.)	197×330×330mm (7 $\frac{3}{4}$ ×13×13in.)	23L (0.8ft ³)	381×584×457.2mm (15×23×18in.)	CE	ETL Intertek	13.6/16.8kg (30/37 lbs)

Measurements are in millimeters. Measurements in () are US Standard, unless stated otherwise.

* Microwave Wattage, IEC 60705 Tested

** Includes door handle



WARRANTIES

Warranty Certificates can be found on the ACP, Inc. website at: www.acpsolutions.com/warranty



ACP's commitment to quality may mean a change in specification without notice.

Visit our website for more information: www.acpsolutions.com