

RCS Series

RESTAURANT LINE

RCS511TS - 1100 Watts, Touch pad control
 RCS511DSE - 1100 Watts, Dial control

FEATURES AND BENEFITS

- 1100 watts of cooking power
 - Quick heating for consistent results
- 34 L (1.2 cubic ft.) oven capacity
 - Accommodates a 356 mm (14") platter
- Motor driven top antenna
 - Reliable distribution of energy for consistent heating results
- Non-removable front air filter
 - Cools componentry, extends life of oven

TOUCH CONTROL MODELS

- 100 programmable menu items, 4 cooking stages, 5 power levels
- Braille touch pads
- Versatile program options
- One-touch cooking

DIAL CONTROL MODELS

- 10:00 light up dial timer
- 4 power levels
- Automatic reset to zero when cooking cycle is interrupted (manual reset available as user option)




*Reliable, long lasting
 Grab 'n Go handle with no
 moving parts*

*Available with
 touch pad or dial
 controls*



IDEAL APPLICATIONS

- Server stations
- Convenience stores
- Coffee shops
- Concessions
- Breakrooms






































BOOST HEATS AND RE-THERMS IN SECONDS!

- Breakfast sandwich reheats in 1:00
- Stage cooking perfectly prepares instant oatmeal in 1:30

SPECIFICATION COMPARISON

MENUMASTER® COMMERCIAL MICROWAVE OVENS

MODEL / UPC CODE	WATTS	POWER SOURCE	PLUG TYPE	CABINET DIMENSIONS (H X W X D)**	CAVITY DIMENSIONS (H X W X D)	CAPACITY	SHIPPING DIMENSIONS (H X W X D)	SAFETY LISTING	SANITATION LISTING	WEIGHT PROD./SHIP
MSO5353 728028315943	3500*	400V, 50Hz, Wye, 16A, 3 phase, 5 wire	IEC 309 	472×650×597mm (18 $\frac{1}{8}$ ×25 $\frac{3}{8}$ ×23 $\frac{1}{2}$ in.)	251×535×330mm (9 $\frac{7}{8}$ ×21×13in.)	45L (1.6ft ³)	565×768×667mm (22 $\frac{1}{4}$ ×30 $\frac{3}{4}$ ×26 $\frac{1}{4}$ in.)			66/73kg (146/161 lbs)
MSO5351 728028315837	3500*	230-240V, 50Hz, 30A, single phase	IEC 309 	472×650×597mm (18 $\frac{1}{8}$ ×25 $\frac{3}{8}$ ×23 $\frac{1}{2}$ in.)	251×535×330mm (9 $\frac{7}{8}$ ×21×13in.)	45L (1.6ft ³)	565×768×667mm (22 $\frac{1}{4}$ ×30 $\frac{3}{4}$ ×26 $\frac{1}{4}$ in.)			66/73kg (146/161 lbs)
MSO5211 728028315820	2100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	472×650×597mm (18 $\frac{1}{8}$ ×25 $\frac{3}{8}$ ×23 $\frac{1}{2}$ in.)	251×535×330mm (9 $\frac{7}{8}$ ×21×13in.)	45L (1.6ft ³)	565×768×667mm (22 $\frac{1}{4}$ ×30 $\frac{3}{4}$ ×26 $\frac{1}{4}$ in.)			66/73kg (146/161 lbs)
MOC5241 705105607306	2400*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	448×346×487mm (17 $\frac{5}{8}$ ×13 $\frac{3}{8}$ ×19 $\frac{3}{16}$ in.)	130×298×216mm (5 $\frac{1}{8}$ ×11 $\frac{3}{4}$ ×8 $\frac{1}{2}$ in.)	8.4L (0.3ft ³)	524×432×559mm (20 $\frac{5}{8}$ ×17×22in.)			32/33kg (70/73 lbs)
DEC21E2 719881167718	2100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	343×419×574mm (13 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×22 $\frac{5}{8}$ in.)	171×330×305mm (6 $\frac{3}{4}$ ×13×12in.)	17L (0.6ft ³)	473×556×625mm (18 $\frac{5}{8}$ ×21 $\frac{7}{8}$ ×24 $\frac{5}{8}$ in.)			30/34kg (67/74 lbs)
DEC18E2 719881159317	1800*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	343×419×574mm (13 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×22 $\frac{5}{8}$ in.)	171×330×305mm (6 $\frac{3}{4}$ ×13×12in.)	17L (0.6ft ³)	473×556×625mm (18 $\frac{5}{8}$ ×21 $\frac{7}{8}$ ×24 $\frac{5}{8}$ in.)			30/34kg (67/74 lbs)
DEC14E2 728028043181	1400*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	343×419×574mm (13 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×22 $\frac{5}{8}$ in.)	171×330×305mm (6 $\frac{3}{4}$ ×13×12in.)	17L (0.6ft ³)	473×556×625mm (18 $\frac{5}{8}$ ×21 $\frac{7}{8}$ ×24 $\frac{5}{8}$ in.)			30/34kg (67/74 lbs)
RFS518TS 728028043181	1800*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	365×551×533mm (14 $\frac{3}{8}$ ×21 $\frac{3}{4}$ ×20in.)	226×359×413mm (8 $\frac{7}{8}$ ×14 $\frac{1}{8}$ ×16 $\frac{1}{4}$ in.)	34L (1.2ft ³)	467×663×581mm (18 $\frac{1}{2}$ ×26 $\frac{1}{8}$ ×22 $\frac{3}{4}$ in.)			32/35kg (69/76 lbs)
RCSS1ITS 728028020762	1100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	352×559×483mm (13 $\frac{7}{8}$ ×22×19in.)	216×368×381mm (8 $\frac{1}{2}$ ×14 $\frac{1}{2}$ ×15in.)	34L (1.2ft ³)	422×640×502mm (16 $\frac{5}{8}$ ×25 $\frac{3}{16}$ ×19 $\frac{3}{4}$ in.)			18.6/21.8kg (41/48 lbs)
RCSS1DSE 728028129489	1100*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	352×559×483mm (13 $\frac{7}{8}$ ×22×19in.)	216×368×381mm (8 $\frac{1}{2}$ ×14 $\frac{1}{2}$ ×15in.)	34L (1.2ft ³)	422×640×502mm (16 $\frac{5}{8}$ ×25 $\frac{3}{16}$ ×19 $\frac{3}{4}$ in.)			18.6/21.8kg (41/48 lbs)
RMS510TS2 728028470246	1000*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	310×512×403mm (12 $\frac{1}{4}$ ×20 $\frac{1}{8}$ ×15 $\frac{7}{8}$ in.)	197×330×330mm (7 $\frac{3}{4}$ ×13×13in.)	23L (0.8ft ³)	381×584×457.2mm (15×23×18in.)			13.6/16.8kg (30/37 lbs)
RMS510DS2 728028470215	1000*	230-240V, 50Hz, 16A, single phase	CEE 7/7 "Schuko" 	310×512×403mm (12 $\frac{1}{4}$ ×20 $\frac{1}{8}$ ×15 $\frac{7}{8}$ in.)	197×330×330mm (7 $\frac{3}{4}$ ×13×13in.)	23L (0.8ft ³)	381×584×457.2mm (15×23×18in.)			13.6/16.8kg (30/37 lbs)

Measurements are in millimeters. Measurements in () are US Standard, unless stated otherwise.

* Microwave Wattage, IEC 60705 Tested

** Includes door handle



WARRANTIES

Warranty Certificates can be found on the ACP, Inc. website at: www.acpsolutions.com/warranty



ACP's commitment to quality may mean a change in specification without notice.

Visit our website for more information: www.acpsolutions.com